

# stage cover 3v9

## TECHNICAL DATA

Diameter	9,21 m
Height	5,51 m
Floor area	37 m <sup>2</sup> / 54 m <sup>2</sup>
Membrane surface front part	n/a
Membrane surface overall	112 m <sup>2</sup>
Construction weight	602 kg
Membrane weight front part	n/a
Membrane weight overall	77 kg
Anchoring	ballast/stakes/anchors

## ENTRANCES

Entrance cover	PVC
Number of entrances	1
Entrance height	2,60 m
Entrance width (floor level)	1,70 m
Entrance width (center)	3,00 m
Ventilation openings	1

## MATERIALS

Construction material	steel (S235JR)
Construction finish	galvanization/powder coating
Strut diameter	4,83 cm
Strut thickness	0,2 cm
Membrane material	PVC
Membrane thickness	690 g/m <sup>2</sup>

## SAFETY

Wind resistance	25 m/s
Extra loads	1000 kg
Membrane certificate	B1, M2 (DIN EN 13501-1)

\*greater loads allowed with prior approval

## ASSEMBLY TIME/EQUIPMENT

Assembly time	6 h
Disassembly time	2 h
Number of technicians	5
Transportation	van/truck
Equipment	crank winch/boom-truck

All sizes in this document are rounded approximations and may deviate due to varying materials and production processes.

